

# GA4000

# Full Height Turnstiles (S/D)

## SPECIFICATION



### Operation Speed

15 to 22 people per minute in a single direction.

### Finish

Galvanised & polyester powder coated

### Key Features

100% duty cycle heavy industrial usage, force tested to 1200N, single phase supply, plug and play installation, programmable control panel, fire alarm input built in as standard (engages from rotation), high specification turnstile to control schools/arenas and unauthorised access to secure areas, seamlessly forms part of the existing fence lines perimeter security, mild or stainless steel for long lasting and maintenance free performance, 90° or 120° rotor assemblies available, bi-directional or single direction only and fail safe or fail secure modes in the event of power failures in the event of power failure.

### Safety Systems

Built in as standard is an anti-trap safety system to stop the possibility of users getting trapped in the turnstile.

### Dimensions

Single: 1410 x 2225 x 1276  
double: 2780x 225 x 1276

### Standard Spec

Galvanised & powder coated, bi-directional, fail safe or fail secure, access reader brackets, passage counter as standard, CE marked, O&M manual and, easy installation.

### Optional Extras

Rain canopy, LED down light, stop/go passage indicators, stainless steel version, special RAL colours and, fork lift bases.

### Construction

Steel and aluminium

### Operation

Fail safe: standard  
Fail secure: optional

